

GKH30**Technical Specifications**

Items	Unit	Parameters
Total length	mm	13000
Total	mm	2490/3590
Total	mm	2910
Axle base	mm	3600
Rated work	m	30
Max. platform	m	28.3
Max. work range	m	24.3
Arm luffing range	°	-12~+80
Bent arm luffing range	°	-65~+70
Arm luffing time	s	40
Arm contraction time	s	70
Max. rotation speed	r/min	0.5
Max. tail swing	mm	1400
Platform size	mm	1800×900×1150
Platform rotation range	°	±90
Turntable rotation radius	mm	2650
Total weight under travel condition	kg	15880
Rated load	kg	150
Max. load	kg	450
Max. travel speed	km/h	5.6
Min. turning radius	m	7
Min. ground clearance	mm	260

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Max. gradeability	%	30
Engine model		YC4D80-T10
Rated engine power	kW/ (r/min)	58/ (2400)
Solid tyre		10.00-20/7.5

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572