

## XCMG LW500F Medium Wheel Loader



Item	Parameter	Unit
Rated load	5.0	t
Bucket capacity	3.0	m <sup>3</sup>
Dumping height	3100	mm
Dumping distance	1274	mm
Max.drawing force	158	kN
Max. traction	156	kN
Dimension	8010×3016×3350	
Operating weight	16.5	t
Boom lifting time	≤5.6	s
Total time of three devices	≤9.9	s

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Wheelbase	2900	mm
Min. turning radius (bucket outer)	6920	mm
Rated power	±35°	
Travel speed	I Gear (Forward/Backward)	0~11.5/16.5 km/h
	II Gear (Forward)	0~38 km/h
<b>Long boom parameter</b>		
	Standard bucket	Coal bucket
Bucket capacity	2.7m <sup>3</sup>	3.5m <sup>3</sup>
Rated load	4.5t	4.0t
Dumping height	3520mm	3340mm
Dumping distance	1230mm	1380mm
Dimension	8300×3016×3350	8530×3016×3350
Min. turning radius (bucket outer)	7060mm	7080mm
Operating weight	16.6t	16.7

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
Post Code: 201100

Website: [www.shlongji.com](http://www.shlongji.com)

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572