

XCMG XCT30E Truck Crane



| Dimensions | Unit | |
|-----------------------------|------------|------------------------------------|
| Overall length | Mm | 12740 |
| Overall width | Mm | 2500 |
| Overall height | Mm | 3480 |
| Weight | | |
| Dead weight in travel state | Kg | 33490 |
| Front axle load | Kg | 7900 |
| Rear axle load | Kg | 25590 |
| Power | | |
| Engine model | | SC8DK280Q3 SC9DF300Q3 WD615.329 |
| Engine rated output | Kw(r/min) | 206/2200 221/2200 213/2200 |
| Engine rated torque | N.m(r/min) | 1112/1400 1250/1400 1160/1100-1600 |
| Travel | | |
| Max.travel speed | Km/h | 80 |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

| | | |
|--|-------|---------|
| Min. turning diameter | M | 22 |
| Min. ground clearance | Mm | 290 |
| Approach angle | ° | 20 |
| Departure angle | ° | 16 |
| Max. gradeability | % | ≥40 |
| Fuel consumption of per 100km | L | ≈37 |
| Lifting performance | | |
| Max. total rated lifting load | T | 30 |
| Min. rated working radius | M | 3 |
| Turning radius at swing table tail | Mm | 3270 |
| Base boom max. load moment | Kn.m | 1128 |
| Base boom | M | 10.6 |
| Full-extend boom | M | 41 |
| Full-extend boom+Jib | m | 49.3 |
| Outrigger longitudinal distance span | M | 5.65 |
| Outrigger lateral distance span | M | 6.0/4.8 |
| Working speed | | |
| Boom elevating time | S | 68 |
| Boom telescoping time | S | 165 |
| Max. slewing speed | r/min | 2.5 |
| Main winch max. speed(single line) | m/min | 120 |
| Auxiliary winch max.speed(single line) | m/min | 120 |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China
Post Code: 201100

Website: www.shlongji.com

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572